Server-wide mail preferences

Preferences | Black List | White List | Mail Queue

General options

Maximum message size [ ] kilobytes

Check the passwords for mailboxes in the dictionary [ ]

Enable message submission [x] (will be enabled on all IP addresses)

Relay options

Relaying

- ( ) closed
- (•) authorization is required:
  - [ ] POP3 lock time [ ] Min
  - [x] SMTP

Webmail

Available Webmail clients

- [x] Horde 4.1.6
- [x] AtMail 1.02

Antivirus preferences

Used antivirus

- ( ) None
- (•) Parallels Premium Antivirus

DomainKeys spam protection

Allow signing outgoing mail [ ]

Verify incoming mail [x]

[ ] Switch on SPF spam protection

SPF checking mode: Reject mail when SPF resolves to "fail" (deny)

SPF local rules

SPF guess rules

SPF explanation text

[x] Switch on spam protection based on DNS blackhole lists

DNS zones for DNSBL service: zen.dnsbl

Separate entries with a semicolon, for example: 'sbl.spamhaus.org;zen.spamhaus.org'

Names for POP3/IMAP mail accounts

- ( ) Use of short (webmaster) and full (webmaster@domain.com) POP3/IMAP mail account names is allowed
- (•) Only use of full POP3/IMAP mail accounts names is allowed

* Required fields

Spam Filter Settings

Settings | Black List | White List

General

Switch on server-wide SpamAssassin spam filtering [x]

Switch on server-wide greylisting spam protection [ ]

Apply individual settings to spam filtering [x]

SpamAssassin Settings

The maximum number of worker spamd processes to run (1-5) * 5

The score that a message must receive to qualify as spam * 5.00

Add the following text to the beginning of subject of each message recognized as spam *****SPAM******

Leave this field blank if you do not want to add any text. Type _SCORE_ if you want to include the score in the message subject.

* Required fields